

Telephone Handset

EXPERIENCE

Entrotec has over 25 years of experience in the design and manufacture of vandal resistant door entry systems.

WARRANTY

Entrotec systems are renowned for their reliability and have a 2 year warranty on all Entrotec manufactured products as standard.

SUPPORT

Entrotec offer complimentary training courses and telephone support.

- H = 210mm W = 100mm D = 50mm
- High Impact White ABS Plastic
- Latching Privacy Switch with Illuminated LED
- Door Open Button with Illuminated LED
- Adjustable Call Tone Volume
- Optional Extension/ Accessories Available



Technical Specification

Privacy	Illuminated Red LED button to indicate privacy on Latch on/off (no timeout) Muted call tone when privacy on
Door Open	Large 20mm door release button Illuminated Green LED button to indicate door open Anti "Lock-Down" feature as standard
Call Tone	Pulsed tone with volume adjust feature as standard
Volume	Adjustable from mute (on Privacy) to 84dB at 13.8VDC Adjustable by internal volume control (measurement taken – distance 100cm orientation 0°)

Power	Operational voltage 10-16VDC 3mA during idling
Power	190mA during call tone
Consumption	9mA per lit LED (Privacy and/or Door Open)
Cable	CAT5 / CW1308 4 pair minimum (leaves 1 spare core)
Note*	*3 pair can be used if Door Open LED function omitted*
Extension	Additional handsets can be fitted (up to 3 in total) Optional extension Beacon available Optional extension Sounder/Beacon available
Accessories	Inductive Coupler available for Hard of Hearing Handset Hook available for Physically Impaired Relay for triggering aux. equipment (pulsed with call tone) Timer for triggering aux. equipment (triggered by call tone)
Note*	*All Extension equipment and Accessories sold separately*

