

# COUPLER

## Inductively Coupled Speech Amplification Unit

### EXPERIENCE

Entrotec has over 25 years of experience in the design and manufacture of vandal resistant door entry systems.

### WARRANTY

Entrotec systems are renowned for their reliability and have a 2 year warranty on all Entrotec manufactured products as standard.

### SUPPORT

Entrotec offer complimentary training courses and telephone support.



The inductively coupled speech amplification unit (COUPLER) operates in conjunction with the resident's hearing aid. When the hearing aid is set in the 'T' position speech being played at the resident's room unit is also played through their hearing aid.

- High quality speech
- Simple Installation
- Easily Retro-fitted
- Surface or Flush Mount with the use of standard double-gang electrical backbox (not supplied)

## Technical Specification

Voltage 12VDC 1A. Plug top transformer provided.

IP Rating Not rated. Internal use only

Range 3 metres free space.

Weight 0.1Kg

Input Single channel, screw terminal  
Connects to S1 & 0V on handset

Dimensions 150mm Width  
90mm Height  
20mm Depth

Temp. Range -25°C to +70°C

Compatibility The Coupler operates with Entrotec's audio and video handsets and apartment stations

Entrotec Limited  
5 Ashwood Court  
Oakbank  
Livingston  
EH53 0TL

www.entrotec.com  
Tel: +44(0) 1506 886230  
Fax: +44(0) 1506 886233  
saleshq@entrotec.co.uk  
Support: 0844 858 6370



**ENTROTEC**

DS024 – Rev 2