

KMS Combined Readers

The KMS range of SimpleKey readers provides all the benefits of the KMS residential access control, for use with either legacy or high Security fobs and I/D devices.



- **Legacy readers** compatible with most types of legacy fobs including KMS Sharktooth PAC, Entrotag etc.
- **HS reader** offers additional security by eliminating the risk of cloning the HS fobs, which will also work with legacy readers (without the additional security).
- **Panel mount and Surface** reader use the industry standard 40mm aperture enables the reader to fit into most new and existing door entry panels.
- **Vandal Resistant** reader employing a robust stainless-steel case and fully potted electronics that can be used in environmentally challenging conditions.
- **Legacy and HS Readers** work with all types of KMS systems and a range of other manufacturers controllers whilst the **BUS readers** only work with SimpleKey 4 systems.
- **Range of LED designs** (Blue/Red/Green) giving a number of engineering functions, as well as whether access is allowed or denied.
- **Robust** British designed and built reader for the UK housing providers and comes with a life time guarantee.

Installation

The **Panel Mount (PM)** reader is designed to be mounted within metal panels, no thicker than 2.0mm with a 40mm square cut-out for the front of the reader.

Dimensions: 55mm × 55mm square by 11mm deep.

The **Vandal Resistant** can be fixed to any non-metallic surface using, the supplied, vandal resistant screws.

Dimensions: 100mm × 100mm square × 13mm deep.

The **Surface Mount** reader is designed to be fixed directly onto a wall or pedestal.

Dimensions: 98mm × 98mm square × 30mm deep.

Connected using standard alarm/1308/Cat 5 or above dependent on type and application.

For further information
please contact KMS on 01494 531099
info@kms.uk.net

1 Marlborough Estate, High Wycombe, Buckinghamshire, HP11 2LB